

kronotex
FLOORS FOR LIVING

*Discover
the floors for living*

COLLECTION 2007



PRODUCT OVERVIEW



Basic

... good for every occasion.

Length: 1380 mm	Width: 193 mm	Thickness: 6 mm
Use Class per EN 685		23
Abrasion Class		AC3
Degree of Use		heavy, private
Example of Application		Hallway



High Use Areas

page 4



Smart

... because life is so colourful.

Length: 1380 mm	Width: 193 mm	Thickness: 7 mm
Use Class per EN 685		31
Abrasion Class		AC3
Degree of Use		moderate, commercial
Example of Application		Small Offices



Low or Occasional Use Areas

page 6



Dynamic

... it varies like the weather.

Length: 1380 mm	Width: 193 mm	Thickness: 8 mm
Use Class per EN 685		32
Abrasion Class		AC4
Degree of Use		medium, commercial
Example of Application		Hotels



Medium Use Areas

page 8



Exquisit

... the solitary one.

Length: 1380 mm	Width: 193 mm	Thickness: 8 + 1 mm
Use Class per EN 685		32
Abrasion Class		AC4
Degree of Use		medium, commercial
Example of Application		Hotels



Medium Use Areas

page 12



These floors are designed with a 45° bevel on the edges. Thus the panels form a V-groove when joined, giving the impression of solid wood planks.



The authentic wood structure, which can be seen, touched and felt, imparts a natural appearance.



This realistic structure really does look like genuine wood. Feel it!

Basic

Basic is the laminate floor for beginners. Only 6mm in thickness, it possesses all the quality and comfort characteristics of durable, long-lasting, and wear-resistant universal flooring, with an almost unlimited range of applications. It is ideal for living spaces with a normal amount of use and with limited installation clearance. Thanks to the **Kronotex** "Clic2Clic" connection system, **Basic** is easily, quickly and cleanly installed, without the use of adhesives. Very economically priced, **Basic** is an especially attractive option for first-time users of laminate. A floor on which one can pleasurably walk through life.



Sutter Oak PR D 742



Merbau PR D 1329



Carolina Red Oak PR D 755



Wild Cherry PR D 1359



Rhone Beech PR D 1403



Canmore Oak PR D 1418



Natural Maple PR D 1465

Pictures are faithful reproduction of patterns and hues.




AC 3 LIVING 23
High Use Areas

Recommended Use Class per EN 685

D 742



D 755, D 1329, D 1359, D 1403,
D 1418, D 1465



kronotex
FLOORS FOR LIVING



D 1465 | Natural Maple

... good for every occasion.



1380 x
193 x
6 mm

2,663 m²



56 Cartons
= 149,15 m²

Smart

Just a little thicker than Basic but almost as economical and a great value for the money. Ideal for moderate, medium, or intensive use in living areas, it is also suitable for commercial areas with moderate or occasional use. And especially for those spaces where every millimeter of clearance counts. With its "Clic2Clic" installation system, **Smart** is easily and quickly installed – like all **Kronotex** laminates.



Ruppian Oak PR D 1210



Beech Nobelle PR D 1424



Merbau PR D 1329



Ticino Walnut PR D 1440



Wild Cherry PR D 1359



Portland Oak PR D 2780



Mountain Maple PR D 1371



Country Oak PR D 1411


Pictures are faithful reproduction of patterns and hues.




AC 3 **COMMERCIAL 31**
Low or Occasional Use Areas

Recommended Use Class per EN 685

D 1210



D 1329, D 1359, D 1371, D 1411,
D 1424, D 1440, D 2780



kronotex
FLOORS FOR LIVING



D 1359 | Wild Cherry

... because life is so colourful.



1380 x
193 x
7 mm

2,397 m²



56 Cartons
= 134,24 m²

Dynamic

Dynamic. This is the laminate floor for universal application and variable use. Of 8mm thickness, with an optimized profile, for uniquely solid and form-fast interlocked connection. In living spaces they sustain even extremely intensive use, in commercial areas with moderate use they have proven their reliability thousands of times over.



Canary Wood WG D 404



Natural Oak WG D 644



Heritage Pekan WG D 406 



Mueritz Maple PR D 654 



Brazilian Cherry WG D 432



Country Noce PR D 725



Carelia Maple WG D 437 



Chestnut PR D 764 



Antique Oak WG D 643



White Beech PR D 856

Pictures are faithful reproduction of patterns and hues.




AC 4 COMMERCIAL 32
Medium Use Areas

Recommended Use Class per EN 685


D 406, D 856




D 404, D 432, D 437,
D 643, D 644



D 654, D 725, D 764



Dynamic floors with  are available ex stock with SOUND DESIGN noise-insulating underlayer.

kronotex
FLOORS FOR LIVING



D 406 | Heritage Pekan

... it varies like the weather.



1380 x
193 x
8 mm

2,131 m²



56 Cartons
= 119,32 m²

Dynamic



Lake Bodensee Cherry PR D 1363



Alder blue BS D 1472



Atlas Cherry PR D 1372



Sacramento Pine WG D 1496 



Constanze Beech PR D 1404 



Larch Filzmoos MO D 2244



Cognac Oak PR D 1412 



Chateau Beech WG D 2404



Merbau Brazil PR D 1460



Chateau Oak WG D 2427



Siberia Birch PR D 1461 




Palisander WG D 2440 

Pictures are faithful reproduction of patterns and hues.


D 1372, D 1472, D 1496, D 2244,
D 2404, D 2427, D 2440, D 2441



D 2457, D 2777, D 2781



D 1363, D 1404, D 1412,
D 1460, D 2776



Dynamic floors with  are available ex stock with SOUND DESIGN noise-insulating underlayer.



Makassar WG D 2441



Vintage Oak WG D 2781



Walnut WG D 2457 🎵



Old Oak WG D 2820



Noah Beech WG D 2776 🎵



Cypress WG D 2777



Pictures are faithful reproduction of patterns and hues.

D 1461

D 2820

Exquisit

Strong, resilient, universal. And at the same time exclusive, elegant, individual. A floor which can take everything – and give even more. Particularly comfortable, variable, flexible. Impossibly attractive. With authentic wood appearance. Fascinating both to the eye and touch. With SOUND DESIGN noise insulation. Complete with new, fascinating designs, structures and traditional V-groove. One which brings opposites together. And raises classic to elite level.



Choco Latte MO | V4 D 2236



Magona ER | V4 D 2770



Vernon Oak ER | V4 D 2241



Stable Oak ER D 2773



Rainier Oak ER | V4 D 2242



Natural Pine MX D 2774



Jatoba MO | V4 D 2282



Noce Linea MX D 2775



Surabaya Oak HS | V4 D 2466

Pictures are faithful reproduction of patterns and hues.



AC 4 **COMMERCIAL 32**
Medium Use Areas

Recommended Use Class per EN 685



D 2236, D 2241, D 2242, D 2282, D 2466,
D 2770, D 2773, D 2774, D 2775




Exquisit floors – always
with SOUND DESIGN
noise-insulating underlayer

kronotex
FLOORS FOR LIVING

D 2770 | Magona

... the solitary one.



Robusto

Robusto combines a high density fiberboard of 12 mm thickness with an especially wear-resistant surface. The "Clic2Clic" tongue-and-groove connection system was developed especially to hold up under the highest encumbrance. Its inherent stability makes it simple, user friendly and easy to lay. Its volume ensures excellent heat and sound insulation.

Its material and manufacturing concept make an ideal floor for extreme conditions – particularly in industrial use.



Treehill Oak Yellow ER D 639



Sacramento Pine WG D1496



Country Noce WG D 725



Walnut WG D 2778



Lake Bodensee Cherry WG D 1363



Portland Oak WG D 2780



Constanze Beech WG D 1404



Muiracatiara WG D 2782



Cognac Oak WG D 1412




Gotland Maple WG D 7467

Pictures are faithful reproduction of patterns and hues.




AC 5 **COMMERCIAL 33**
High Use Areas
Recommended Use Class per EN 685




D 1496, D 2778, D 2782,
D 7467



D 639



D 725, D 1363, D 1404,
D 1412, D 2780





kronotex
FLOORS FOR LIVING

D 639 | Treehill Oak Yellow

... top of its class!



Mega

It's the flooring with extra large panels for coverage of spacious rooms and for especially quick installation. Its surface treatment is also eye-catching: traditional stone patterns as well as design ideas like stone and Mediterranean tile. Special format, distinctive appearance: **Mega** is the flooring for uncommon taste and cost-conscious needs.



Stonehenge TI D 975



Varese TI D 2817



Canberra ER D 2826



Venecia TI D 1277



Sandstone TI D 2818




Stratos orange TI *D 2827



Cesena TI D 2811



Travertin ST D 2819



Stratos anthrazit TI *D 2828



Sargasso Slate ER D 2815



Kimberly ER D 2825



Sahara Stone TI D 2816


Pictures are faithful reproduction of patterns and hues.




AC 4 **COMMERCIAL 32**
Medium Use Areas
Recommended Use Class per EN 685



D 975, D 1277, D 2811, D 2815, D 2816,
D 2817, D 2818, D 2825, D 2826



D 2819



D 2827, D 2828



connection technology



D 975 | Stonehenge

... for beginners & advanced.

1302 x 326 x 8 mm
*D 2827/2828:
644 x 326 x 8 mm

2,122 m²
*2,100 m²



45 Cartons
= 95,50 m²
*48 Cartons
= 100,80 m²

Amazone

Refined, classy, stylish and boundless in laying variation: **Amazone**, the extraordinarily narrow, long floorboard flooring line. A floor that makes a dashing eccentric impression – fascinating to look at, individually fashionable, flexible in arrangement and handling.



Red Core Beech MO | V4 D 2201



Parisienne Oak ER | V4 D 2323



Mahogany MO | V4 D 2390



Kempas MO | V4 D 2391



Oklahoma Oak ER | V4 D 2432



Teak classic MO | V4 D 2443



Brazilian Cherry MO | V4 D 2444



Cambridge Oak ER | V4 D 2461



Red Oak WG | V4 D 2771



Canadian Maple MO | V4 D 2772



Cumbrian Maple MO | V4 D 2779

Pictures are faithful reproduction of patterns and hues.



AC 4

COMMERCIAL 32
Medium Use Areas

Recommended Use Class per EN 685

ER =




D 2201, D 2323, D 2390, D 2391, D 2432, D 2443,
D 2444, D 2461, D 2771, D 2772, D 2779



D 2391 | Kempas

... the style conscious choice.





Mammut

Stunning in looks, strong in use, high in value: A floor with previously unattained panel size, strength and quality. This flooring is therefore ideally suited to applications and interiors with the highest aesthetic, quality and handling requirements, whether private, commercial or official and prestigious.

The **Mammut** decors are particularly fascinating: elegant floor boards with country cottage character and the authentic look, structure and colouring of natural wood.



Red Core Beech MO | V4 D 2201



Teak classic MO | V4 D 2443



Barnwell Oak ER | V4 D 2235



Barrique Oak ER | V4 D 2462



Wenge WG | V4 D 2412




Stable Oak ER | V4 D 2773



Limed Oak ER | V4 D 2413



Pacific Merbau MO | V4 D 2442




Pictures are faithful reproduction of patterns and hues.



AC 5 COMMERCIAL 33
High Use Areas

Recommended Use Class per EN 685



D 2201, D 2235, D 2412, D 2413,
D 2442, D 2443, D 2462, D 2773





D 2442 | Pacific Merbau

... timeless elegance.



STRONG ARGUMENTS FOR KRONOTEX

Kronotex is one of the first among the world leaders to present the new "Clic2Clic" generation in connection technology in a complete line of beautiful non-adhesive flooring systems for the most varied needs and uses, from individual to universal. These have been greeted with enthusiasm on five continents.

And there are good reasons why they have convinced users:



Kronotex floors are easy care and hard-wearing. Neither dirt nor harmful bacteria become lodged in them.



Kronotex floors are flame resistant.



Kronotex floors are largely resistant to cigarette embers.



Kronotex floors are non fading and retain their brilliance over many years.



Kronotex floors are rugged, load and impact resistant.



Kronotex floors are abrasion resistant and suitable for casters.



Kronotex floors are produced from natural sustainable raw materials and contain no harmful chemical substances.



Kronotex floors are comfortable underfoot and of course also available with footfall sound insulation.



Kronotex floors are well suited for installation over subfloor heating.




Kronotex floors are stain resistant.

STRUCTURES



PR (wood pore) – typical wood structure



ER (registered emboss) – genuine wood appearance due to consistence between pattern and embossing



MO (matt oiled) – matt oiled surface appearance



HS (hand-scraped) – surface like that of stripped floorboards



WG (wood grain) – rustic embossing



TI (tiles) – tile appearance with original joint pattern



MX (matrix) – deep structure embossing with typical wood matt/gloss contrast



ST (stone) – distinctive stone surface

ACCESSORIES

Kronotherm TS 5 mm
Footfall sound insulation board
1 piece = 800 x 675 mm
20 pieces = 10,8m²



Ktex Underlay Mat



Ktex Fixing System
for Ktex Skirtings 1 and 4 – 6



Ktex Rosettes for Radiator



Ktex Laminat Cleaner



Ktex Repair Paste
different colours



Ktex Installation Set
1 crowbar, 1 push block, spacer




Ktex Silicone
different colours



Ktex Felt Pads





KRONOTHERM TS
Footfall Sound Insulation Board for parquet and laminate flooring
Le panneau d'isolation phonique pour parquet et sols stratifiés
Die Raumklangplatte für Parkett und Laminatböden

Environmentally friendly, made of natural mineral fibres
Ecofriendly product in line with the motto "Umweltfreundlich, aus natürlichen Rohstoffen"

Special, special designed for skaters and skaters
Résistance à la pression (développé spécialement pour les patineurs de vitesse et les skieurs)

Sound insulation according to EN ISO 15708
Isolation acoustique selon la norme EN ISO 15708

Footfall sound reduction from 15 dB to 18 dB
Atténuation de la réduction phonique de 15 à 18 dB

Thickness: 5 mm
Contains: 20 pieces / 10,80 m²

KRONOTHERM TS
Package content: 20 pieces Length: 800 mm Width: 675 mm Thickness: 5 mm Area: 10,80 m²
Contenu: 20 Panneaux Longueur: 800 mm Largeur: 675 mm Epaisseur: 5 mm Surface: 10,80 m²
Inhalt: 20 Platten Länge: 800 mm Breite: 675 mm Dicke: 5 mm Fläche: 10,80 m²

Footfall Sound Insulation Board for parquet and laminate flooring
Le panneau d'isolation phonique pour parquet et sols stratifiés
Die Raumklangplatte für Parkett und Laminatböden


kronotex
Distribution: Kronotex, Vertrieb: Kronoplus GmbH & Co. KG, Kronoply Chemies, Kronoply Holzgerätschaften, Kronoply Holzwerkstoffe
www.kronotex.de
www.kronoplus.de
www.kronoply.de
PEFC
PINO KRONO GROUP

... for a professional installation


ACCESSORIES




Ktex 1
15 x 58 x 2400 mm




Ktex 2
19 x 17 x 2400 mm




Ktex 3
16,5 x 16,5 x 2400 mm




Ktex 4
20 x 40 x 2400 mm



Ktex 5
15 x 70 x 2400 mm



Ktex 6
15 x 80 x 2400 mm



Ktex 7
15 x 90 x 2400 mm

Outer corners, inner corners and end pieces are available for profiles Ktex 1 and Ktex 4.



Ktex 4 Outer Corners



Ktex 4 Inner Corners



Ktex 1 End Pieces




Ktex Fixing System
for Ktex Skirtings 1 and 4 – 6

Skirtings



Ktex Motion Profile – HDF
7–13mm, Length: 2700mm / 900 mm



Ktex Motion Profile – Aluminium
7–13mm, Length: 2700mm / 900 mm



Ktex Transition Profile – HDF
7–13mm, Length: 2700mm / 900 mm



Ktex Transition Profile – Aluminium
7–13mm, Length: 2700mm / 900 mm



Ktex End Profile – HDF
7–13mm, Length: 2700mm / 900 mm



Ktex End Profile – Aluminium
7–13mm, Length: 2700mm / 900 mm



Ktex Stair Profile – HDF
7–9mm, Length: 2700mm / 1350 mm



Ktex Stair Profile – Aluminium
7–9mm, Length: 2700mm / 1350 mm

HDF / Aluminium Profiles

PRESENTATION



Tower 18



Tower 12



MDF Display twin modul

MDF Display triple modul



Decoflag
40 x 200 cm



Big Swing



Little Combo





Displays / sample portfolios

TECHNICAL INFORMATION

Kronotex laminates consist of at least four stable layers which ensure the extraordinary durability and unique quality of **Kronotex** floors.



- ① The top surface of the flooring consists of a specially resistant protective overlay film. This is fused with an attractive resinated decorative film into a practically abrasion-proof, hardwearing surface.
- ② Extremely dense HDF fiberboard forms the supportive core (HDF, E1).
- ③ On the undersurface of the core a dampness-impeding stabilization film ensures and preserves the high structural stability of **Kronotex** laminates.
- ④ All **Exquisit** and selected **Dynamic** floorings are fitted with an additional "Sound Design" underlay to minimise footstep and ambient noise.

IT'S WHAT'S UNDERNEATH THAT MATTERS

Once you have decided for a laminate floor, when quality and appearance are a perfect fit, then you need to check the requirements for perfect installation. The suitability of the subfloor is very important.

Suitable:

- ◆ old flooring such as wood, firmly-adhering PVC, dry ceramic, linoleum
- ◆ cement screed (max. residual moisture: 2.0 CM%)
- ◆ anhydrite cement and anhydrite flow cement screed (max. residual moisture: 0.3 CM%)
- ◆ magnesia screed (max. residual moisture: 3.0 CM%)
- ◆ Have a screed specialist in your area give you a residual moisture report!

Wet and damp rooms, saunas, carpeting and xylolith are not suitable subfloors.

The subfloor must be dry, level, firmly affixed and clean. Minor unevenness can be compensated with an underlay mat or – if exceeding 3 mm/m – sanded down or leveled with a filler.

UNDERFLOOR HEATING – OF COURSE!



Kronotex laminate floors can be readily installed upon warm water underfloor heating, serve well and even help to save on heating costs. Simply observe these conditions carefully:

- ◆ Be sure to heat mineral underlays before flooring installation to eliminate any excess dampness.
- ◆ Have a heating specialist in your area give you a heating report.
- ◆ Ensure that during installation, the surface temperature of the floor is at least 15°C (60°F).
- ◆ For dampness insulation and as a vapor barrier, use a (0.2mm) PE film underlayment. For sound absorption you can use PE foam, **Kronotex** underlay mat or **Kronotex** Laminate flooring with "Sound Design".
- ◆ At the beginning of each heating period, when you first turn on the underfloor heating, raise the temperature gradually in 5°C (9°F) increments per day until you reach the desired temperature. The floor's surface temperature should not exceed 26°C (80°F).

CLEANING AND CARE

Kronotex flooring is not only hygienic but also very easy to look after. Here is some advice:

1. Sweep the dry floor with a soft broom or use a vacuum cleaner.
2. Marks and dirt can be wiped off with a slightly damp cloth, following the grain of the plank. For stubborn marks, please use Kronotex cleaner.
3. Please use felt pads under furniture and soft rubber castors on chairs.
4. Place door mats in special areas (hall, entrance). In industrial buildings, provide footwells.
5. Minor damage to the floor can easily be repaired with the Kronotex repair kit. In case of more serious damage, please consult a specialist.

Detailed instructions for installing **Kronotex** floors are available free on DVD and of course at our homepage:

www.kronotex.de



QUALITY CONTROL

Quality can be measured. It is determined and defined according to strict international norms and established in testing, standards, and characteristics profiles. But purchasers and users want more than this. They want clear statements or better yet: clear, contractual guaranties. How far a company meets these demands says something about its seriousness and more: about its confidence in its own product.

The complex "Clic2Clic" profile geometries are recorded, compared and evaluated using the latest in coordinate technology.



**No compromise quality
requires maximum precision!**

“PRINCIPLE Q” – YOUR GUARANTEE

Collections	Guarantee private	Guarantee commercial
Basic	6 years	–
Smart	8 years	2 years
Dynamic	12 years	3 years
Exquisit	12 years	3 years
Robusto	15 years	5 years
Mega	12 years	3 years
Amazon	12 years	3 years
Mammut	15 years	5 years

Kronotex GmbH & Co. KG

(in the following: **Kronotex**) provides buyers in addition to the unencumbered guarantee under law, an additional guarantee covering the abrasion resistance of the floor's surface.

It extends from the date of purchase and covers the products as follows:

CONDITIONS OF GUARANTEE

Kronotex laminate panels must be checked before and during installation for any defects. No liability is accepted for laminate flooring installed despite visible defects.

Kronotex laminate floors must be installed properly according to the instructions, in a dry room, and in accordance with the respective use class. No liability is accepted for **Kronotex** laminate floors installed in damp rooms.

Abrasion areas on **Kronotex** laminate floors must be clearly visible and at least 1cm² in size. And in particular the design layer must be completely abraded. No liability is accepted for abrasion on the edges of the elements or for unusual or improper use, and in particular for damage caused by mechanical stress.

Validity of guarantee is dependent on regular cleaning and maintenance of **Kronotex** floors as described in the care instructions.

Claims under guarantee are valid only if submitted within 30 days of ascertaining damage and accompanied by the original receipt from the retailer. In investigating a guarantee claim, **Kronotex** retains the right to examine the floor in question on site.

OUR GUARANTEE

In cases falling under guarantee, **Kronotex** will deliver a replacement for the damaged element. If the flooring in question is no longer available, then the buyer can choose a replacement of equal value from the current **Kronotex** product line.

Since an annual 10% depreciation in the value of **Kronotex** laminates can be assumed, delivery of a compensation product is dependent on payment of the appropriate difference by the buyer.

No liability is accepted for further damages, especially consequential damages such as those incurred during installation or removal, or transport costs for damaged **Kronotex** laminate floors.

TECHNICAL DATA

Test	Test Norm	Characteristics
Formaldehyde Emission	EN 717-1	< 0,05 ppm
Surface Stain Resistance	EN 438-2, 15	Grade 5, no visible changes to surface
Lightfastness	EN ISO 105-B02 EN 20 105-A02	≥ Level 6 on the Blue Wool Scale (Blauwollskala) ≥ Level 4 on the Grey Scale
Resistance to Cigarette Embers	EN 438-2, 18	Grade 4, no visible changes to surface
Fire Resistance	DIN 4102, 14	Ignites with difficulty, Building Material Class B1
Elevation Difference between connected Elements	DIN EN 13329	Average: ≤ 0,10 mm max: ≤ 0,15 mm
Edge Straightness (Bend)	DIN EN 13329	≤ 0,3 mm/m
Space between connected Elements	DIN EN 13329	Average: ≤ 0,15 mm max: ≤ 0,20 mm
Impression after consistant Loading	EN 433	No visible changes, i.e. <0.01 mm Impression in test with straight steel cylinder of radius 11.3 mm




Manufacture and product control are in accordance with DIN norm EN 13329. The right to technical modifications is reserved. As of April 2007.

Kronotex GmbH & Co. KG

is a member of the following associations and organizations:



kronotex
FLOORS FOR LIVING



kronotex
F L O O R S F O R L I V I N G

As a worldwide leader in the manufacturing of laminate flooring, **Kronotex** offers not only innovative products of top quality, but also assists with extensive logistics, its distribution network and a knowledgeable customer service.

We will be pleased to answer your questions concerning our **Kronotex** laminate flooring. Just ask for our free information material!

Kronotex GmbH & Co. KG
Wittstocker Chaussee 1
D-16909 Heiligengrabe
Germany
Tel. +49 (0) 33962-69 150
Fax +49 (0) 33962-69 288
sales.floor@kronotex.de
www.kronotex.de

Kronotex USA, LLC
810 Technology Drive
Barnwell, SC 29812
U.S.A.
Tel. +1-803-224-9150
Fax +1-803-541-3299
sales@kronotexusa.com
www.kronotexusa.com

Swiss Krono Group



www.kronotex.de